

TECHNICAL SPECIFICATION

HEAD PROTECTION



Visilite® Orange LED Lighting

EVO 2 / 3 / 4 / 5 / 6100 / Code: AHV855-000-800



DESCRIPTION

The VisiLite® helmet illumination system has been developed as a method of increasing worker visibility without dazzling colleagues in close proximity. VisiLite® offers three lighting modes to suit the user's needs with visibility up to 50m. Mode 1: Static (9hrs Approx.) - Mode 2: Slow Flash (190hrs Approx.) - Mode 3: Fast Flash (150hrs Approx.)

OPTIONS

EVO 2 / 3 / 4 / 5 / 6100 (AHV855-000-800)

EVOLite® (AHV860-000-800)

DOWNLOADS

 [Image Pack \(ZIP\)](#)

VIDEO

 youtu.be/TTBu5vC5_x8



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspssafety.com / Web: www.jspssafety.com
Do Not Publish without written permission from JSP Limited. Contact copyright@jspssafety.com.
Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.
Page 1 of 2 / Issued 17 Nov 2020 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.



COMPATIBLE PRODUCTS

EVO®2 Mid Peak OneTouch™ Slip Ratchet Non Vented
EVO®2 Mid Peak OneTouch™ Slip Ratchet Vented
EVO®3 Micro Peak OneTouch™ Slip Ratchet Non Vented
EVO®3 Micro Peak OneTouch™ Slip Ratchet Non Vented Linesman
EVO®3 Micro Peak OneTouch™ Slip Ratchet Vented
EVO®3 Micro Peak Revolution® Wheel Ratchet Non Vented
EVO®3 Micro Peak Revolution® Wheel Ratchet Non Vented Linesman
EVO®3 Micro Peak Revolution® Wheel Ratchet Vented
EVO®3 Mid Peak Revolution® Wheel Ratchet Non Vented
EVO®3 Mid Peak OneTouch™ Slip Ratchet Non Vented
EVO®3 Mid Peak OneTouch™ Slip Ratchet Vented
EVO®3 Mid Peak Revolution® Wheel Ratchet Vented
EVO®5 DualSwitch™ Micro Peak Revolution® Wheel Ratchet Vented
EVO®5 Olympus® Mid Peak Revolution® Wheel Ratchet
EVO®5 Olympus® Mid Peak Revolution® Wheel Ratchet Vented
EVO®5 Olympus® Mid Peak Revolution® Wheel Ratchet Vented Linesman
EVO® 6161 Full Brim Wheel Ratchet
EVO Lite® Micro Peak OneTouch™ Slip Ratchet Non Vented
EVO Lite® Micro Peak OneTouch™ Slip Ratchet Non Vented Linesman
EVO Lite® Micro Peak OneTouch™ Slip Ratchet Vented
EVO Lite® Micro Peak Revolution® Wheel Ratchet Non Vented
EVO Lite® Micro Peak Revolution® Wheel Ratchet Non Vented Linesman
EVO Lite® Micro Peak Revolution® Wheel Ratchet Vented
EVO Lite® Micro Peak Revolution® Wheel Ratchet Vented Linesman
EVO Lite® Mid Peak OneTouch™ Slip Ratchet Non Vented
EVO Lite® Mid Peak OneTouch™ Slip Ratchet Vented
EVO Lite® Mid Peak Revolution® Wheel Ratchet Non Vented
EVO Lite® Mid Peak Revolution® Wheel Ratchet Vented
EVO Lite® Skyworker™ Micro Peak Revolution® Wheel Ratchet Vented

SPECIFICATIONS



Type
Helmet



Minimum Temperature
-10°C



Maximum Temperature
+50°C

Conformity

Does not affect conformity of JSP EVO® helmets to EN397

Attachment System

Slotted rail Clip

Material

ABS Casing & TPU (Thermoplastic Polyurethane) Band

Battery Type

Rechargeable lithium-ion battery (3.7V - 130mA)



Product Weight
42g

RANGE

EAD ACCESSORIES



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com
Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com.
Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.
Page 2 of 2 / Issued 17 Nov 2020 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.

