

LFX[®]

DataSheet

LITHIUM-ION BATTERY FIRE EXTINGUISHER RANGE

The LFX range has been specifically designed to tackle lithium-ion battery fires across a wide range of applications. In addition to primary fire risks, the LFX fluorine-free range of fire extinguishers also protect from secondary A-class fires that have been caused by the exploding batteries.

FX-LI-003-MCF	
Agent	LFX
Capacity (litres)	3
Fire performance	Pending - 13A
Working pressure (bar) @ 20°C	15
Maximum service pressure PS (bar)	20
Temperature range °C	+5 to +60
Discharge time (secs) @ 20°C	25 - 30
Cylinder	Lined steel
Pending certification	BS EN3 Kitemark, MED, MSR, PED, UKCA, CE

FX-LI-006-MCF	
Agent	LFX
Capacity (litres)	6
Fire performance	Pending - 27A
Working pressure (bar) @ 20°C	15
Maximum service pressure PS (bar)	20
Temperature range °C	+5 to +60
Discharge time (secs) @ 20°C	47 - 53
Cylinder	Lined steel
Approved certification	NTA 8133
Pending certification	BS EN3 Kitemark, MED, MSR, PED, UKCA, CE

FX-LI-009-MCF	
Agent	LFX
Capacity (litres)	9
Fire performance	Pending - 34A
Working pressure (bar) @ 20°C	15
Maximum service pressure PS (bar)	20
Temperature range °C	+5 to +60
Discharge time (secs) @ 20°C	72 - 78
Cylinder	Lined steel
Approved certification	NTA 8133
Pending certification	BS EN3 Kitemark, MED, MSR, PED, UKCA, CE



COMMANDEREDGE

PRODUCT CODE

FX-LI-003-MCF
FX-LI-006-MCF
FX-LI-009-MCF

PRODUCT GROUP

CommanderEDGE Extinguishers

DIMENSIONS (mm)(height x width x diameter)

FX-LI-003-MCF: 435 x 188 x 441
FX-LI-006-MCF: 568 x 206 x 510
FX-LI-009-MCF: 622 x 228 x 572

WEIGHT

FX-LI-003-MCF: 5.8kg
FX-LI-006-MCF: 10kg
FX-LI-009-MCF: 14.3kg

- Fluorine free foam concentrate
- 3ltr, 6ltr and 9ltr available
- Easy and ergonomic operation
- Economical maintenance and service

