

TECHNICAL SPECIFICATION

WORKING AT HEIGHT



K2™ 3-Point Harness

K2™ 3-Point Harness / Code: FAR0402



DESCRIPTION

The premium K2™ harness range combines quality materials with innovative features for optimum ergonomic performance, comfort, and safety.

This harness has a work positioning belt, parking loops and quick release buckles, with air mesh material and lightweight aluminium connectors.

OPTIONS

K2™ 3-Point Harness (FAR0402)

DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [Declaration of Conformity \(PDF\)](#)

VIDEO

 youtu.be/_QUfxDLufkA



FEATURES



Quick Release Buckles

Quick release buckles for quick and effortless fitting.



Breathable Material

Air mesh material gives harnesses breathability and anti-tangle feature.



Tool Keepers

K2™ 3-point and 5-point harnesses feature tool keepers for safely stowing tools.



Inspection Labels

Inspection labels and user information protected in PVC pouch.



Lanyard Keepers

Breakaway clips safely store unused lanyards and release in the event of a fall.



Ultimate Comfort

Polyester padding in leg, back and waist areas for improved comfort.

SAFETY STANDARDS

EN 361

EN 358

SPECIFICATIONS

Anchorage Points

2

Adjustment

Shoulder, Chest and Legs

Fall Indicator

No

Quick Release Buckles

Yes

Work Positioning Belt

Yes

Tool Keeper

Yes

Comfort Padding

Shoulders & Legs

Lanyard Parking

Yes

Sub-Pelvic Strap

Yes

Product Label

Protected

Metal Parts

Light Alloy Steel



Rated Weight / Load

140kg



Product Weight

2210g

APPLICATIONS

Geo Technical

Steel Frame

Telecomms

RANGE



COMPATIBLE PRODUCTS

10m Rope & Grab

10m Wire Self-Retractable Lifeline

10m Wire Self-Retractable Lifeline Sharp Edge

15m Wire Self-Retractable Lifeline

20m Rope & Grab

20m Wire Self-Retractable Lifeline

Spartan™ 2m Adjustable Single Fall Arrest Lanyard

Spartan™ 2m Adjustable Twin Fall Arrest Lanyard

2m Self-Retractable Lifeline with Scaffold Hook

2m Self-Retractable Lifeline Sharp Edge

Pioneer™ 2m Single Sharp Edge Fall Arrest Lanyard

2m Steel Cable Anchorage Sling

Pioneer™ 2m Twin Sharp Edge Fall Arrest Lanyard



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspssafety.com / Web: www.jspssafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspssafety.com.

Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 17 Dec 2020 / Copyright 2018 - 2020, JSP Limited. All Rights Reserved.



2m Adjustable Work Positioning Lanyard with Rope Grab
5m Wire Self-Retractable Lifeline
5m Wire Self-Retractable Lifeline Sharp Edge
5m Adjustable Work Positioning Lanyard with Rope Grab
EVO®5 DualSwitch™ Micro Peak Revolution® Wheel Ratchet Vented
EVO® VISTAlens® DualSwitch™ Micro Peak Revolution® Wheel Ratchet Vented
EVO® VISTAshield® DualSwitch™ Micro Peak Revolution® Wheel Ratchet Vented
EVO Lite® Skyworker™ Micro Peak Revolution® Wheel Ratchet Vented
K2™ 2m Single Fall Arrest Lanyard
K2™ 2m Twin Fall Arrest Lanyard
Pioneer™ 2m Single Fall Arrest Lanyard
Pioneer™ 2m Twin Fall Arrest Lanyard
Pioneer™ 2m Adjustable Work Positioning Lanyard
Spartan™ 2m Single Fall Arrest Lanyard with Scaffold Hook
Spartan™ 2m Twin Fall Arrest Lanyard
Spartan™ 2m Adjustable Work Positioning Lanyard

ACCESSORIES

Aluminium Scaffolding Hook
Aluminium Tower Hook
Aluminium Triple Lock Karabiner
Aluminium Twist Lock Karabiner
scaffolders-tool-lanyard
Single Tool Lanyard
Steel Screw Gate Karabiner
Steel Twist Lock Karabiner
Twin Tool Lanyard

