




Compact and lightweight safety goggle offering protection against liquid droplets as well as impacts. The low-profile design enhances the field of vision and a comfortable fit is guaranteed thanks to the fully adjustable head strap.





INNER SEAL





IT ET NODED IT IN

KEY FEATURES

- + Ultra slim design
- ✤ Soft PVC comfort frame

- + Fully adjustable pivoted head strap
- + High performance TECTON 400 anti-scratch and anti-fog protection

LENS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR ()	RLY00161	2C -1.2 ॡ 1BTKN €€/ Z87+ U6	₹ EN 166 3BT 點(€ / Z87+	Impacts, Liquid Droplets	K&N Anti-scratch + Anti-fog / UV400 / Moisture repellent





GENERAL SPECIFICATION

LENS BASE	6mm
WEIGHT	56g

PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	5
PER CARTON	100

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES	
LENS	Polycarbonate	Durable and hard wearing	
FRAME	Thermoplastic Elastomers (TPE)	Lightweight	
HEADBAND	Woven Elastic	Adjustable	

LENS & FRAME MARKINGS

LENS MARKINGS

LENS FILTER TYPE:

2, 2C UV \mid 4 IR filter \mid 5, 6 Solar filter \mid 1.7 to 7 Welding filter if no shade number

SCALE NUMBER (SHADE):

 1.2 Clear or Amber
 1.4 Blue or I/O Waterproof

 1.7 Minimises or I/O
 2.5 Grey or Revo
 3.1 Dark Grey or Mirror

R Identity of manufacturer

OPTICAL CLASS:

1 High optical quality

MECHANICAL STRENGTH:

- S Increased strength
- F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
- B Medium energy impact, resists a 6mm, 0.86g ball at 120m/s
- A High energy impact, resists a 6mm, 0.86g ball at 190m/s
- T Protection against high-speed particles at extreme temperatures

PERFORMANCE:

- 8 Short circuit electric arc
- 9 Molten metal splash
- **K** Resistance to scratches by fine particles
- N Resistance to fogging

CE Certification mark

FRAME MARKINGS

R Identity of manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:

- S Increased strength
- F Low energy impact, resists a 6mm, 0.86 g ball at 45m/s
- B Medium energy impact, resists a 6mm, 0.86 ball at 120m/s
- A High energy impact, resists a 6mm, 0.86 ball at 190m/s
 T Protection against high-speed particles at extreme temperatures

PERFORMANCE

- 3 Liquid droplets or splashes
- 4 Large dust particles > 5 μm
- 5 Gases and small dust particles < 5 µm
- 8 Short circuit electric arc
- 9 Molten metal and hot solids

LK CE Certification marks

USA (ANSI)

LENS: U6 UV (All lenses) L2.5 Solar (Grey)

L1.3 LED L3 Solar (Dark Grey)

k Grey) K Grey K Grey K Grey

LENS AND FRAME:

Z87+ High velocity impact, 0.25 inch, 1.04g ball at 150ft/s

AUS (AS/NZS)

LENS MARKINGS:

OCULAR CATEGORY:

0 UV 1 Solar 2 Solar

3 Solar O Outdoor untinted

MECHANICAL STRENGTH: I Medium energy impact, resists a 6mm, 0.86g ball at 45m/s

FRAME MARKINGS

AS/NZS 1337.1: 2010 guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

CERTIFICATION

Product conforms to the requirement of: UK Regulation 2016/425 on PPE, brought into UK Law and amended & Regulation (EU) 2016/425 of the European Parliament and of the Council as Personal Protective Equipment (PPE).

Type-Examination, (Module B), Certificates issued by: UK - INSPEC International Ltd. 56 Leslie Hough Way, Salford, Greater Manchester M6 6AJ UK [A.B. No. 0194]. EU - INSPEC International B.V. Beechavenue 54, 1119 PW, Schiphol-Rijk, Netherlands [N.B. No. 2849]

Authorised Representative [EU]: Globus EMEA Ltd., 51 Dawson Street, Dublin, D02 AN25, Ireland.

www.riley-eyewear.com

E: info@riley-eyewear.com

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UK



