TECHNICAL SPECIFICATION

WORKING AT HEIGHT



2m Self-Retractable Lifeline with Scaffold Hook

2m Self-Retractable Lifeline with Scaffold Hook / Code: FAR0731



DESCRIPTION

2m lightweight self-retractable lifeline, in robust and durable plastic casing. Webbing width 21mm with shock absorber. Equipped with 1 quarter turn gate aluminium connector and 1 aluminium scaffold hook.

Horizontal use (Sharp Edge VG 11 RFU CNB/P/11.060), fall factor 2 use in the limit of 100kg.

OPTIONS

2m Self-Retractable Lifeline with Scaffold Hook (FAR0731)

DOWNLOADS

- Image Pack (ZIP)
- Declaration of Conformity (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England. Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon. Page 1 of 2 / Issued 17 Dec 2020 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.



COMPATIBLE PRODUCTS

1m Webbing Anchorage SlingAerialine™ 20m Horizontal Lifeline2m Steel Cable Anchorage Sling2m Webbing Anchorage SlingK2™ 2-Point HarnessK2™ 3-Point HarnessK2™ 5-Point HarnessPioneer™ 2-Point HarnessPioneer™ 2-Point QR HarnessPioneer™ 3-Point HarnessSpartan™ 1-Point HarnessSpartan™ 2-Point HarnessSpartan™ 3-Point HarnessSpartan™ 3-Point Harness

ACCESSORIES

Aluminium Scaffolding Hook Aluminium Tower Hook Aluminium Triple Lock Karabiner Aluminium Twist Lock Karabiner Steel Screw Gate Karabiner Steel Twist Lock Karabiner

SAFETY STANDARDS

EN 360

SPECIFICATIONS	
	Fall Indicator No
	Length 2m
	Material 21mm Wide Webbing
	Shock Absorber External
	Sharp Edge Yes
	Casing Robust and Durable Plastic
Xkg	Rated Weight / Load 140kg (100kg For Horizontal and Fall Factor 2 Use)
	Product Weight 1244g
	Delivered With 1 Quarter Turn Aluminium Connector. Gate Opening 21mm. Conforms to EN362 Class B. 1 Aluminium Scaffold Hook. Gate Opening 60mm. Conforms to EN362 Class A/T
APPLICATIONS	
Aeronautics	
Steel Frame	

Wind Turbines

RANGE

SELF RETRACTABLE LIFE LINE



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England. Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon. Page 2 of 2 / Issued 17 Dec 2020 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.

