

# RILEY

# STREAM EVO™


Stream Evo safety glasses provide extreme comfort and 'wearability' with a range of lens options to suit a variety of conditions.



TempFLEX™



SOFT TPE



ADJUSTABLE NOSE BRIDGE



LIGHTWEIGHT



DIELECTRIC

## KEY FEATURES

- + Single wraparound polycarbonate lens
- + Soft, ventilated TempFLEX™ temple tips provide a comfortable, secure fit
- + Slim temples enhance comfort when worn with ear defenders
- + Lateral protection
- + 100% metal free
- + Soft, adjustable, anti-slip nose bridge
- + Supplied with a microfibre storage pouch
- + Stream Evo Accessory Pack available separately. Contains adjustable headband & gasket
- + Also available in a smaller size - see Stream™ Evo Small
- + Also available without plastic packaging - see Stream™ (Evo) Eco

LENS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS	
CLEAR	○ RLY00361	2C-1.2 R 1FTKN CE / Z87+ U6 / IO 0	R EN 166 FT US CE / Z87+ / AS/NZS 1337.1 Lic. SMK40933	Impacts, UV radiations	TECTON 400 K&N Anti-scratch & Anti-fog / UV400 / Moisture repellent	
GREY	● RLY00362	5-2.5 R 1FTKN CE / Z87+ U6 L2.5 / I2		Impacts, UV & Solar radiations		
BLUE	● RLY00365	2C-1.4 R 1FTKN CE / Z87+ U6 S / I1		Impacts, UV radiations		
AMBER	● RLY00371	2-1.2 R 1FTKN CE / Z87+ U6 / I0		Impacts, UV radiations		
LED	● RLY00369	2C-1.4 R 1FTKN CE / Z87+ U6 L1.3 / I1		Impacts, UV radiations		
ANTI-REFLECTIVE	○ RLY00363	2C-1.2 R 1FT CE / Z87+ U6 / IO 0		Impacts, UV radiations	FRIDA 400 Anti-scratch + Anti-fog / UV400 / Moisture repellent	
TWILIGHT	● RLY00364	5-1.7 R 1FT CE / Z87+ U6 L1.7 / I1		Impacts, UV radiations		
SHADE 3	● RLY00375	3 R 1FKN CE / Z87+ W3 / I3		R EN 166 FT US CE / Z87+	Impacts, UV & Infrared radiations	TECTON 400 K&N Anti-scratch & Anti-fog / UV400 / Moisture repellent
IRG	● RLY00374	4-4 R 1FTKN CE / Z87+ W4				
SHADE 5	● RLY00376	5 R 1FKN CE / Z87+ W3				
ACCESSORY PACK	RLYA0017	N/A	N/A	N/A	N/A	

## GENERAL SPECIFICATION

LENS BASE	9.5mm
WEIGHT	23g

## PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

## COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	One piece moulded lens with side protection
NOSE BRIDGE	Thermoplastic Elastomers (TPE)	Comfortable and flexible
TEMPLE	TR90 Thermoplastic / Thermoplastic Elastomers (TPE)	Co-injected - Robust, flexible, lightweight and ventilated
HINGE	TR90 Thermoplastic	Metal free and durable

## LENS & FRAME MARKINGS

### LENS MARKINGS

**LENS FILTER TYPE:**  
2, 2C UV | 4 IR filter | 5, 6 Solar filter | 1.7 to 7 Welding filter if no shade number

### SCALE NUMBER (SHADE):

1.2 Clear or Amber    1.4 Blue or I/O Waterproof  
1.7 Minimises or I/O    2.5 Grey or Revo    3.1 Dark Grey or Mirror

 Identity of manufacturer

### OPTICAL CLASS:

1 High optical quality

### MECHANICAL STRENGTH:

**S** Increased strength  
**F** Low energy impact, resists a 6mm, 0.86g ball at 45m/s  
**B** Medium energy impact, resists a 6mm, 0.86g ball at 120m/s  
**A** High energy impact, resists a 6mm, 0.86g ball at 190m/s  
**T** Protection against high-speed particles at extreme temperatures

### PERFORMANCE:

**8** Short circuit electric arc  
**9** Molten metal splash  
**K** Resistance to scratches by fine particles  
**N** Resistance to fogging

 Certification mark

### FRAME MARKINGS

 Identity of manufacturer

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

### MECHANICAL STRENGTH:

**S** Increased strength  
**F** Low energy impact, resists a 6mm, 0.86 g ball at 45m/s  
**B** Medium energy impact, resists a 6mm, 0.86 ball at 120m/s  
**A** High energy impact, resists a 6mm, 0.86 ball at 190m/s  
**T** Protection against high-speed particles at extreme temperatures

### PERFORMANCE

**3** Liquid droplets or splashes  
**4** Large dust particles > 5 µm  
**5** Gases and small dust particles < 5 µm  
**8** Short circuit electric arc  
**9** Molten metal and hot solids

 Certification marks

### USA (ANSI)

#### LENS:

**U6** UV (All lenses)    **L1.3** LED    **L1.7** Solar (I/O, Twilight)  
**L2.5** Solar (Grey)    **L3** Solar (Dark Grey)    **W4** Infrared lens

#### LENS AND FRAME:

**Z87+** High velocity impact, 0.25 inch, 1.04g ball at 150ft/s

### AUS (AS/NZS)

#### LENS MARKINGS:

#### OCULAR CATEGORY:

**0** UV    **1** Solar    **2** Solar  
**3** Solar    **O** Outdoor untinted

#### MECHANICAL STRENGTH:

**I** Medium energy impact, resists a 6mm, 0.86g ball at 45m/s

#### FRAME MARKINGS:

**AS/NZS 1337.1: 2010** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

### CERTIFICATION

Product conforms to the requirement of: UK Regulation 2016/425 on PPE, brought into UK Law and amended & Regulation (EU) 2016/425 of the European Parliament and of the Council as Personal Protective Equipment (PPE).

**Type-Examination, (Module B), Certificates issued by: UK** - SGS Limited., Rossmore Business Park, Ellesmere Port Cheshire CH65 3EN UK. [A.B. No. **0120**].  
**EU** - SGS FIMKO OY., Takomotie 8, 00380 HELSINKI, Finland [N.B. No. **0598**]

**Authorised Representative [EU]:** Globus EMEA Ltd., 51 Dawson Street, Dublin, D02 AN25, Ireland.



Standard Mark  
(SAI Global)

[www.riley-eyewear.com](http://www.riley-eyewear.com)

**E:** info@riley-eyewear.com

**T:** +44 (0)161 877 4747

**F:** +44 (0)161 877 4746

Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UK

