

TECHNICAL SPECIFICATION

HEAD PROTECTION



EVOGuard®M Forestry Helmet Systems

EVOGuard®M2 Forestry Helmet System / Code: AKE24A-400-800



DESCRIPTION

The EVOGuard®M Forestry browguard and helmet systems are innovative solutions to protect the wearer in a multitude of high risk working environments. All EVOGuard® visor components are fully compatible with a range of existing EVO® helmet models.

OPTIONS

EVOGuard®M2 Forestry Helmet System (AKE24A-400-800)

EVOGuard®M3 Forestry Helmet System (AKE24A-500-800)

DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [Declaration of Conformity \(PDF\)](#)


VIDEO



JSP Limited. Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com
Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com.
Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.
Page 1 of 3 / Issued 17 Nov 2020 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.



FEATURES



Visor Range

Two high performance complete forestry systems are available, enabling users to select the perfect visor for their task and price point.



Balanced & Secure

Fitted to a browguard or helmet, the self-lubricating nylon hinges hold the visor securely in position even during extreme movement, whilst offering balanced, even weight distribution.



Dual Layer Protection

The EVOGuard®M Forestry Helmet and Forestry Browguard Systems both feature a secondary layer of eye protection in the form of the integrated EVOSpec® polycarbonate retractable eyeshield.



Product Compatibility

Designed to maximise compatibility with a broad range of JSP products, such as the Force™8 respirator with PressToCheck™, Springfit™ disposable masks and the Sonis® helmet mounted ear defender range.



Supreme Comfort

Features an easy to use Revolution® wheel ratchet and a 3D adjustment harness, which offers 1-2-3 point depth settings for increased adaptability to ensure a perfect, secure fit.



Coverage

EVOGuard® visors provide comprehensive facial coverage without limiting movement or vision.

SAFETY STANDARDS
























EN 397

EN 352-3

EN 1731

EN 166

SPECIFICATIONS

	Peak Standard
	Impact Resistance 50 Joules
	Lateral Deformation Yes
	Molten Metal Yes
	Maximum Temperature +50°C
	Minimum Temperature -40°C
	ABS Shell Yes
	Textile Harness
	Depth Adjustment 3D Harness
	Wheel Ratchet Yes
	Ventilation Yes
	Reflective Option Fitted
	Integrated Eyewear Fitted
	ID card holder Optional
	Optional 2 point chinstrap (EN397 & EN 812 compliant) Optional
	Optional 4 point chinstrap (EN397 Compliant) Optional
	Mounting Helmet
	SNR 31 dB
	Cup Material ABS
	Adjustable Yes
	Hygiene Hygiene Kit
	Manufacturer's Trademark JSP Dagger
	Increased Robustness resists a 22mm, 43g steel ball travelling at 5.1 metres per second. This is derived from the practical test which is to drop the ball (as stipulated) from a height of 1.3 metres. S

COMPATIBLE PRODUCTS

EVO® Goggle Double Lens

EVO® Goggle Single Lens

Flexinet® Mask FFP2 (821)

Flexinet® Mask FFP2OV (823)

Flexinet® Mask FFP2V (822)

Flexinet® Mask FFP3 Valved (832)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.
Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jssafety.com / Web: www.jssafety.com
Do Not Publish without written permission from JSP Limited. Contact copyright@jssafety.com.
Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.
Page 2 of 3 / Issued 17 Nov 2020 / Copyright 2018 - 2020, JSP Limited. All Rights Reserved.



Force™ 8 Half Mask Respirator

SpringFit™ Disposable Dust Mask 421ML FFP2

SpringFit™ Disposable Dust Mask 425ML FFP2 with Typhoon™ Valve

SpringFit™ Disposable Dust Mask 431ML FFP3

SpringFit™ Disposable Dust Mask 435ML FFP3 with Typhoon™ Valve

SpringFit™ Disposable Dust Mask 436ML FFP3 with Typhoon™ Valve and Nuisance Carbon Layer

Sonis® Compact Helmet Mounted Ear Defenders

Sonis®1 Helmet Mounted Ear Defenders

Sonis®3 Helmet Mounted Ear Defenders

Stealth™ 16G

Stealth™ 7000

Stealth™ 8000

Stealth™ 9000

Thermex™ Double Lens Goggle

Typhoon™ Moulded Mask FFP2 Valved (725)

Typhoon™ Moulded Mask FFP2OV (726)

Typhoon™ Moulded Mask FFP3 Valved (735)

ACCESSORIES

Quick Release 4 Point Linesman Harness

Sonis® Compact Helmet Mounted Ear Defenders

Sonis® Compact Hygiene Kit


Sonis®1 Helmet Mounted Ear Defenders

Sonis®1 Hygiene Kit

Sonis®3 Helmet Mounted Ear Defenders


Sonis®3 Hygiene Kit


PPE Cleaning Station & Accessories

 Visible Light Transmittance (VLT)
70%

 Visor Length
18cm

Material
ABS Frame and Woven Stainless Steel Mesh Visor

 BSI Kitemark
Yes

 Recyclable
Yes

 JSPCheck
Yes

 Product Weight
805g

APPLICATIONS

Agricultural

- Arborist
- Farming
- Landscaping

Forestry & Landscaping

RANGE



BRANDING

Front

