



Dry



Wet



Heat



Oily



Cold



Chemical



TG5010

A lightweight Cut D glove with a generous cuff length for use in dry conditions. The thin palm dipped X-Dura coating and close fitting design ensures hands can move freely making it an ideal choice for general handling tasks with risk of cut.

Key Features

- Highly cut resistant
- Breathable seamless liner to eliminate perspiration
- Provides excellent grip and abrasion resistance in dry conditions

Ideal for

- Automotive
- Construction and Utility
- Engineering and Manufacturing
- Warehousing and Logistics

Sizes:	6-12	Gauge:	13gg
Liner:	Polyamide/PPE/Glass	Coating:	X-Dura PU
No/Bag:	10	No/Carton:	100

TG5010

Glove Specifications

Glove lengths
220mm-270mm

Glove Weight
13 gauge

Liner Type
Polyamide/HPPE/Steel/Elastane

Glove colour
Pantone 368c / R:92 G:193 B:81 / C:63 M:0 Y:100 K:0

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

Coating Specifications

Coating colour
Black

Dip type
X-Dura Polurethane

Dip Application
Palm Dipped

Glove Treatment
X-Dura



Packaging Information

Qty/bag
10 pairs

Qty/carton
100 pairs

Carton Dimensions
300mm x 600mm x 200mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.