

## **FESTOON**

### 110V EXTENDABLE FESTOONS

Our Connectable Festoon Kit range now includes 12m, 22m and 50m lengths. All kits use our unique connector and can be joined in any combination, up to a total length of 150m. This makes extending the festoon on site simple and easy, saving time and money.













- Designed in the UK by Red Arrow
- Extendable up to 150m long
- Robust, high efficiency LED heads
- Pre-wired with industrial 3 pin plug
- IK07 rated for site applications



#### **Specification**

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
FKF50100W	Festoon Kit Connectable 20-Way 50m	11000lm		100W	110 lm/W

#### **Product Information**

Warranty	2 Years
Colour Appearance (CCT)	6000K
IP Rating	IP44
IK Rating	IK07
Voltage	110V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra >80

Colour Finish	Yellow RAL1007
LED Life Expectancy	L70B50 35,000 Hours
Power Factor	0.9
Frequency	50Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class I
Working Temperature	-20°C to 40°C

Tel: 0114 279 8999

Email: sales@redarrowelectrical.co.uk

redarrowelectrical.co.uk



# **FESTOON**

## 110V EXTENDABLE FESTOONS


#### **Packaging Information**


Dimensions (mm)	L: 50m Head: H: 60 x Ø: 75 mm	
Product Net Weight (kg)	4.4 kg	
Barcode	5055807624367	
Box Dimensions (mm)	L: 340 x W: 340 x D: 160 mm	
Box Gross Weight (kg)	9.4 kg	

Units/Outer Carton	2	
Outer Carton Barcode	15055807624364	
Outer Carton Dimensions (mm)	L: 700 x W: 355 x D: 180 mm	
Outer Carton Gross Weight (kg)	10.3 kg	









Tel: 0114 279 8999

Email: sales@redarrowelectrical.co.uk

redarrowelectrical.co.uk