Safety Signs & Supplies. Product Data Sheet



Proplex Flame Retardant



Product Specification	
Material	Fluted Flame Retardant Polypropylene
Colour	Translucent or Black
Weight (g/m²)	2mm – 250gsm 3mm – 380gsm 4mm – 700gsm
Tolerance	+/-5%
Water resistant	Yes
Recyclable	Yes
Recycled Content	Black FR Proplex Sheets – 25% recycled content
Environmental Product Declaration	S-P-02268 (Full EPD available on request)

Range

Available sizes and product codes:

Size	Code
1.2m x 2.4m	
1.2m x 50m	Various
0.85m x 2m	

Twin wall, impact resistant sheets or rolls are used to protect most floor finishes. Available in several thicknesses and weights that can be selected based on site traffic and project duration.

Features & Benefits

- Strong, durable and lightweight
- Can be cut easily and creates no harmful dust
- ◆ Waterproof, non-toxic and resistant to chemicals
- Tear, puncture and impact-resistant
- Can be custom printed

Applications

- Floor protection
- Door protection
- Window/Curtain walling protection
- Worktop protection

Certification



Flame Retardant – Approved to LPS1207 – Certificate Number 843a/03

Installation Instructions/Guidelines

- ◆ Dependent on application
- Please contact our technical team for specific advice

Handling & Storage

Store in ambient conditions

End Of Life Recovery

Compatible with the Closed Loop Re-Manufacturing Scheme.



Tel Number: 01245 327 397 Email: sales@safetysigns.uk.com Website: www.safetysigns.uk.com