TECHNICAL SPECIFICATION

WORKING AT HEIGHT

JSP

Pioneer[™] 3-Point Harness

Pioneer[™] 3-Point Harness / Code: FAR0204



DESCRIPTION

3-point harnesses are designed for use in applications requiring a work positioning element, such as for telecoms engineers. This harness is lightweight, features the Pioneer[™] range combination of black and grey for ease of identification between the shoulder and leg straps, and comes with a padded back support for extra comfort.

OPTIONS

Pioneer™ 3-Point Harness (FAR0204)

DOWNLOADS

- Image Pack (ZIP)
- Declaration of Conformity (PDF)

VIDEO

by youtu.be/37Q_1s4H2-M



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon. Page 1 of 5 / Issued 17 Nov 2020 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.



Safety Retainers

Features rigid plastic retainers to store excess strap length safely.

SAFETY STANDARDS

EN 361

EN 358

SPECIFICATIONS	
	Anchorage Points 2
	Adjustment Shoulders, Chest and Legs
	Fall Indicator Yes
	Quick Release Buckles No
	Work Postioning Belt Yes
	Tool Keeper Yes
	Comfort Padding No
	Lanyard Parking No
	Sub-Pelvic Strap Yes
	Product Label Protected
	Metal Parts Light Alloy Steel
Xkg	Rated Weight / Load 140kg
	Product Weight 1900g
APPLICATIONS	
Cranes	
Forms	
Linesman	

RANGE





Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon. Page 2 of 5 / Issued 17 Nov 2020 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.



Fall Indicator

Visual identification shows harness has been subjected to a fall, for easier inspection.



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England. Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon. Page 3 of 5 / Issued 17 Nov 2020 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.





Lightweight

Lightweight alloy steel hardware for strength, comfort, and convenience.



Inspection Labels

Inspection labels and user information protected in PVC pouch.



Points of Adjustment

Full body harness adjustment points that cover universal sizes.

COMPATIBLE PRODUCTS

10m Rope & Grab 10m Wire Self-Retractable Lifeline 10m Wire Self-Retractable Lifeline Sharp Edge 15m Wire Self-Retractable Lifeline 20m Rope & Grab 20m Wire Self-Retractable Lifeline Spartan[™] 2m Adjustable Single Fall Arrest Lanyard Spartan[™] 2m Adjustable Twin Fall Arrest Lanyard 2m Self-Retractable Lifeline with Scaffold Hook 2m Self-Retractable Lifeline Sharp Edge Pioneer[™] 2m Single Sharp Edge Fall Arrest Lanyard Pioneer[™] 2m Twin Sharp Edge Fall Arrest Lanyard 2m Adjustable Work Positioning Lanyard with Rope Grab 5m Wire Self-Retractable Lifeline 5m Wire Self-Retractable Lifeline Sharp Edge 5m Adjustable Work Positioning Lanyard with Rope Grab EVO®5 DualSwitch™ Micro Peak Revolution® Wheel Ratchet Vented EVO® VISTAlens® DualSwitch™ Micro Peak Revolution® Wheel Ratchet Vented EVO® VISTAshield® DualSwitch™ Micro Peak Revolution® Wheel Ratchet Vented EVOLite® Skyworker™ Micro Peak Revolution®Wheel Ratchet Vented K2[™] 2m Single Fall Arrest Lanyard K2[™] 2m Twin Fall Arrest Lanyard Pioneer[™] 2m Single Fall Arrest Lanyard Pioneer[™] 2m Twin Fall Arrest Lanyard Pioneer™ 2m Adjustable Work Positioning Lanyard Spartan[™] 2m Single Fall Arrest Lanyard with Scaffold Hook Spartan™ 2m Twin Fall Arrest Lanyard



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England. Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon. Page 4 of 5 / Issued 17 Nov 2020 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.



ACCESSORIES

Aluminium Scaffolding Hook Aluminium Tower Hook Aluminium Triple Lock Karabiner Aluminium Twist Lock Karabiner scaffolders-tool-lanyard Single Tool Lanyard Steel Screw Gate Karabiner Steel Twist Lock Karabiner Twin Tool Lanyard



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England. Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon. Page 5 of 5 / Issued 17 Nov 2020 / Copyright 2018 - 2020. JSP Limited. All Rights Reserved.

