TECHNICAL SPECIFICATION

RESPIRATORY PROTECTION



Jetstream® Constructor Kits

Jetstream®TH2P R SL Constructor Kit / Code: CBP020-000-000



DESCRIPTION

Jetstream® is a belt-mounted rechargeable respirator with a large capacity disposable filter supplying filtered air through a highly flexible reinforced hose to a variety of head tops for different applications.

The Jetstream® Constructor kit carry case contains: Mk®7 Safety Helmet complete with sealed polycarbonate visor Flexible hose

TH2P R SL dust or TH2A2P R SL gas and dust filters Flow meter

Rechargeable battery Multi-region plug adaptor

OPTIONS

Jetstream®TH2P R SL Constructor Kit (CBP020-000-000)

Jetstream® TH2A2P R SL Constructor Kit (CDP020-000-000)

DOWNLOADS

Image Pack (ZIP)

Declaration of Conformity (PDF)









FEATURES



Comfort

Waist mounted blower unit with fully automatic alarm and integrated battery attached to a wide comfortable waist belt.



Adaptable

A wide range of kits, filters and head tops are available to suit a variety of tasks.



High Performance Filters

TH2P R SL (A Reusable Solid & Liquid, Particulate Aerosol Filter)

COMPATIBLE PRODUCTS

Replacement Jetstream® Dust & Gas Filter TH2A2P R SL Replacement Skirt for Jetstream® Helmet Jetstream® MK®7 Helmet

ACCESSORIES

Replacement Jetstream® Bayonet Coupling Black Replacement Jetstream® Dust & Gas Filter TH2A2P R SL Replacement Skirt for Jetstream® Helmet Jetstream® MK®7 Helmet Replacement Visor for Jetstream® MK®7 Headpiece

PPE Cleaning Station & Accessories

SAFETY STANDARDS

EN 12941

EN 397

EN 166

SPECIFICATIONS



Impact Resistance

50 Joules



Molten Metal

Yes

Maximum Temperature

+50°C

Minimum Temperature

-20°C



HDPE Shell

Yes



Recyclable

Shell



Harness



Slip Ratchet



Slip



Ventilation No



Integrated Eyewear





Optional 2 point chinstrap (EN397 & EN 812 compliant)

Optional



Manufacturer's Trademark JSP Dagger



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)

Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum



protection for goggles. В



Protection from Liquid Droplets

3



Resistance to Molten Metals and Hot Solids (optional)



BSI Kitemark

Yes



JSPCheck

Yes

Classification TH2 (Turbo Hood)

R (Reusable)

Minimum Filtration Efficiency

Maximum Total Inward Leakage (TIL)

2% When Fitted To Jetstream

Nominal Protection Factor


50


UK Assigned Protection Factor


















Face Seal Type Hypoallergenic Material **Exhalation Valve** Yes Mask Design A Turbo Hood Powered Air Purifiying Respirator (Loose Fitting) Latex free No Metal Free No Battery Type 8 Hour Rechargable Nickel Metal Hydride (NiMH) Product Weight Head Top 884g Noise Level 65dB Filter Type P (Protects Against Solid and Liquid Aerosols) *** Gas Filters Not Compatible *** **Product Weight** Power Pack & Filter 1066g **Product Weight**

APPLICATIONS

Construction and Infrastructure

TH2P R SL Filter 124g

RANGE

Jetstream^a







