

EN 407:2004



X 2 X X X X



Dry



Wet



Heat



Oily



Cold



Chemical



# NGT1060

A flexible, highly comfortable double dip X-Dura Nitrile waterproof glove with an extended cuff providing a secure fit and additional cut protection. Ideal for outdoor construction and civil engineering.

## Key Features

- Flexible and very comfortable
- Waterproof
- Superb grip
- Hot contact resistance up to 250°C

## Ideal for

- Construction and Utility
- Engineering and Manufacturing
- Oil and Gas
- Waste, Recycling and Local Authority
- Warehousing and Logistics

<b>Sizes:</b>	7-11	<b>Gauge:</b>	15gg
<b>Liner:</b>	Nylon	<b>Coating:</b>	LiquiDex
<b>No/Bag:</b>	10	<b>No/Carton:</b>	100

# NGT1060

## Glove Specifications

### Glove lengths

220mm-270mm

### Glove Weight

15 gauge

### Liner Type

Nylon

### Glove colour

Pantone 1795c / R:223 G:59 B:48 / C:8 M:96 Y:100 K:1

### Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

## Coating Specifications

### Coating colour

Black

### Dip type

Flat Nitrile

### Dip Application

Knuckle Dipped

### Glove Treatment

LiquiDex



## Packaging Information

### Qty/bag

10 pairs

### Qty/carton

100 pairs

### Carton Dimensions

290mm x 440mm x 280mm

## Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

### Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

### Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.