

TECHNICAL SPECIFICATION

WORKING AT HEIGHT



Spartan™ 2m Adjustable Work Positioning Lanyard

Spartan™ 2m Adjustable Work Positioning Lanyard / Code: FAR0308



DESCRIPTION

Work positioning and restraint lanyard, adjustable up to 2m, made from 14mm polyamide 3-strand rope (complying with ISO 1140).

OPTIONS

Spartan™ 2m Adjustable Work Positioning Lanyard (FAR0308)

DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [Declaration of Conformity \(PDF\)](#)



COMPATIBLE PRODUCTS

1m Webbing Anchorage Sling
Aerialine™ 20m Horizontal Lifeline
2m Steel Cable Anchorage Sling
2m Webbing Anchorage Sling
K2™ 3-Point Harness
K2™ 5-Point Harness
Pioneer™ 3-Point Harness
Spartan™ 3-Point Harness

ACCESSORIES

Aluminium Scaffolding Hook
Aluminium Tower Hook
Aluminium Triple Lock Karabiner
Aluminium Twist Lock Karabiner
Steel Screw Gate Karabiner
Steel Twist Lock Karabiner

SAFETY STANDARDS

EN 358

SPECIFICATIONS

Length
2m Max.

Material
14mm Polyamide 3 Strand Twisted Rope (Complying To ISO 1140). Black and Red Tracer In The Rope To Indicate Degradation of Material.

Rope Ends
Stitched and Covered With Polyethylene Protective Sleeve. Abrasion Resistant Thimbles Provided Within Loops

Protective Rope Sleeve
No

Adjustment Device
Manual Ring Type Adjuster Of Forged Alloy Steel



Product Weight
770g

Delivered With
2 Screw Gate Connectors In Alloy Steel. Gate Opening 18mm. Conforms To EN362 Class B & M.

APPLICATIONS

MEWP
Window Cleaning

RANGE

WORK POSITIONING LANYARDS

