

DataSheet


With one of the widest ranges available on the market today, Commander® is firmly established as a true market leader. Time has proved these portable fire extinguishers as a dependable choice for almost any situation, and reliable performance is guaranteed. Furthermore the Commander® 6ltr, 9ltr, 6kg and 9kg models now boast extremely high fire ratings as well as the British Kitemark Certification.




AFFF (Aqueous Film Forming Foam) extinguishers offer some additional benefits over water units. Not only do they typically have higher fire ratings, but they are also suitable for Class B fires involving flammable liquids. They are highly effective extinguishers with a rapid flame knockdown, and do not compromise visibility for safe building evacuation.

Our range consists of a 6 litre with a 21A 144B fire rating, and a 9 litre with a 27A 183B rating. Both units are 35kVa dielectrically tested and safe for inadvertent use on fires involving live electrical equipment. The units are Kitemarked and come with our full 5-year warranty.

Technical Specification	FSEX1	FSEX3	FSWX6	FSWX9
Capacity	1 litre	3 litre	6 litre	9 litre
Fire Rating	5A 21B	13A 55B	21A 144B	27A 183B
Extinguishing Medium	AFF Foam	AFF Foam	AFF Foam	AFF Foam
Working Pressure	14 bar	12 bar	14 bar	14 bar
Temperature Range	+5°-+60°C	+5°-+60°C	+5°-+60°C	+5°-+60°C
Cylinder Material	Steel	Steel	Steel	Steel
Pressuring Gas	Nitrogen	Nitrogen	Nitrogen	Nitrogen











PRODUCT CODE

FSEX1 | FSEX3 | FSWX6 | FSWX9

PRODUCT GROUP

Commander® Extinguishers

DIMENSIONS (mm) (height x width x diameter)

FSEX1: 340 x 120 x 105 FSEX3: 430 x 260 x 140 FSWX6: 525 x 180 x 280 FSWX9: 620 x 180 x 560

WEIGHT

FSEX1: 2kg FSEX3: 5.3kg FSWX6: 9.3kg FSWX9: 14.2kg

- Fully CE marked
- Kitemarked to BS EN3*
- Plastic base for protection (excludes 1 & 2 ltr)
- Corrosion-resistant finish
- Polyethylene internal lining
- Brass spray nozzle
- Full range of spare parts available







*On the 6ltr, 9ltr models only