

TG6240

Conforming to cut level E under the new EN388:2016 standard, TG6240 has unrivalled levels of dexterity and comfort and is designed to last for long periods of time.

The MicroDex Ultra coating and new Life Extending Technology makes the TG6240 perfect for high cut risk tasks in wet, dry and oily conditions. Also features a thumb crotch to further extend the wear life of the glove.

The LXT range is certified as carbon neutral. This means that at no extra cost, your LXT glove has zero negative impact on the environment, to the point of delivery.

Key Features

- LXT Engineering triple wrapped core for extra cut protection and a soft luxurious feel for the wearer
- Hot contact resistance up to 100°C
- LXT treatment for water, oil and dirt resistance and reduced staining
- Reinforced thumb crotch for enhanced longevity
- A breathable 15gg liner, making the glove highly dexterous & tactile
- Touchscreen compatible

Ideal for

- Automotive
- Construction and utility
- Engineering and manufacturing
- Oil and gas
- Rail
- Mechanical and electrical
- Waste, recycling and local authority

KEY

- Dry
- Wet
- Heat
- Oily
- Cold
- Chemical



RECYCLED CARD PACKAGING



TOUCHSCREEN READY

EN 388	4X44E
Sizes	6-11
Liner	Polyester/Glass HPPE/Steel/ Nylon/Elastane
Gauge	15gg
Coating	MicroDex Nitrile
Conditions	

EN 388:2016

4 X 4 4 E

ASTM ANSI CUT LEVEL

A5

EN 407:2004

X 1 X X X X

Qty/band	10 pairs
Qty/carton	100 pairs

