



Dry



Wet



Heat




Oily



Cold



Chemical



TG5140

A close fitting and flexible Cut C glove with a high tech MicroDex Nitrile Foam coating that provides excellent grip in wet dry and oily conditions. Reinforced thumb crotch provides additional durability and glove life.

Key Features

- A highly popular glove, proving very comfortable and long lasting
- MicroDex coating provides safe and reliable grip in wet, dry and oily conditions
- Reinforced thumb crotch for extra protection and longevity
- Seamless knitted liner and palm dip coating allows for ultimate breathability

Ideal for

- Automotive
- Construction and Utility
- Engineering and Manufacturing
- Food Manufacturing and Prep
- Warehousing and Logistics
- Rail
- Waste, Recycling and Local Authority

Sizes:	6-11	Gauge:	13gg
Liner:	Polyamide/PPE/Glass	Coating:	MicroDex Nitrile
No/Bag:	10	No/Carton:	100

TG5140

Glove Specifications

Glove lengths
220mm-270mm

Glove Weight
13 gauge

Liner Type
Polyamide/HPPE/Glass fibre

Glove colour
Pantone 368c / R:92 G:193 B:81 / C:63 M:0 Y:100 K:0

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

Coating Specifications

Coating colour
Black

Dip type
MicroDex Nitrile

Dip Application
Palm Dipped

Glove Treatment
MicroDex



Packaging Information

Qty/bag
10 pairs

Qty/carton
100 pairs

Carton Dimensions
290mm x 440mm x 280mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.